















































# WEST SYSTEM®













## Product Pictures, Discriptions and Codes September 2010














WEST SYSTEM Resin & Hardeners		
	<b>100 Support Pack</b> Ideal to complement the Junior Pack and, when combined with that pack, creates a kit capable of completing most small repair jobs. Contents include 403, 406 and 407 fillers, glue brushes, mixing sticks, graduated mixing pots, gloves, syringes and glass tape.	<b>100 = 1 Pack</b>
	<b>101 Mini Pack</b> Contains a selected mix of materials used to complete smaller repairs around the boat, in the workshop or at home. Contents include: 250g 105 Resin, 50g 205 Hardener, 403 & 407 fillers, dispensing syringes, application tools, gloves and instructions.	<b>101 = 1 Pack</b>
	<b>104 Junior Pack</b> A 600g pack of WEST SYSTEM epoxy (105/205). Designed for the small users.	<b>104 = 1 Pack</b>
	<b>105-K Glass fibre Boat Repair Kit</b> This kit includes all the materials required to complete a range of repairs to glass fibre boats. Contents: 250gm 105 resin, 50gm 205 hardener, 402 milled glass, 409 microspheres blend, Three mixing cups, One Reusable mixing stick, Two pairs nitrile gloves, Two glue brushes, Two syringes, 1m x 125mm 450g/m <sup>2</sup> biaxial glass tape, 1m x 75mm 175g/m <sup>2</sup> plain weave glass tape, 1m x100mm peel ply, Instructions.	<b>105-K = 1 Pack</b>
	<b>A Pack</b> 1kg of 105 resin with 0.2kg of 205 or 206 hardner	<b>A Pack = 1.2kg</b>
	<b>B Pack</b> 5kg of 105 resin with 1kg of 205 or 206 hardner	<b>B Pack = 6.0kg</b>
	<b>C Pack</b> 25kg of 105 resin with 5kg of 205 or 206 hardner	<b>C Pack = 25kg</b>
	<b>E Pack</b> 225kg of 105 resin with 45kg of 205 or 206 hardner	<b>E Pack = 270kg</b>
	<b>105 Epoxy Resin</b> 105 Epoxy Resin® is the base material on which all West System 105 System epoxy compounds are built. The resin is a clear, pale yellow, low-viscosity liquid epoxy resin. Formulated for use with West System hardeners, it can be cured in a wide temperature range to form a high-strength solid with excellent moisture resistance.	<b>105A = 1.0 kg</b> <b>105B = 5.0kg</b> <b>105C = 25kg</b> <b>105E = 225kg</b>
	<b>205 Fast Hardener</b> 205 Fast Hardener® is a medium-viscosity epoxy curing agent. It is used in a majority of situations, at lower temperatures and to produce a rapid cure that develops its physical properties quickly at room temperature. When mixed with the 105 Resin in a five-part resin to one-part hardener ratio, the cured resin/hardener mixture yields a rigid, high-strength, moisture-resistant solid with excellent bonding and coating properties.	<b>205A = 0.2kg</b> <b>205B = 1.0kg</b> <b>205C = 5.0kg</b> <b>205E = 45kg</b>













	<p><b>206 Slow Hardener</b> 206 Slow Hardener® is a low-viscosity epoxy curing agent for use when extended working and cure time is needed or to provide adequate working time at higher temperatures. When combined with 105 Resin in a five-part resin to one-part hardener ratio, the cured resin/hardener mixture yields a rigid, high-strength, moisture-resistant solid with excellent bonding and coating properties.</p>	<p>206A = 0.2kg 206B = 1.0kg 206C = 5.0kg 206E = 45kg</p>
<b>WEST SYSTEM Special Application Hardeners</b>		
	<p><b>207 Special Coating Hardener</b> 207 Special Coating Hardener® is formulated for use with WEST SYSTEM 105 Resin for coating applications where an extremely clear finish is desired. This hardener also provides excellent adhesion for bonding applications. 207 contains an ultraviolet inhibitor to protect the 105/207 mix against sunlight. However, the cured epoxy surface still requires long-term UV protection with a quality marine paint or a UV filtered two part varnish.</p>	<p>207A = 0.29kg 207B = 1.45kg 207C = 7.2kg 207E = 64.5kg</p>
	<p><b>209 Extra Slow Hardener</b> 209 Extra Slow Hardener™ is formulated for use with WEST SYSTEM Brand 105 Resin for general coating and bonding applications in extremely warm and/or humid conditions or when extended working time is desired at room temperature. Provides approximately twice the working time of 206 Slow Hardener. Forms a clear, amber-colored solid with good physical properties and moisture resistance for bonding and coating applications.</p>	<p>209A = 0.29kg 209B = 1.45kg 209C = 7.2kg 209E = 64.5kg</p>
<b>WEST SYSTEM Speciality Epoxy</b>		
	<p><b>G5 Five-Minute Adhesive</b> An easy to use two part, fast setting resin/hardener system. This adhesive is ideal for quick repairs and general bonding around the boat and in the home, the workshop or garage. It is suited for spot applications to hold component parts in position whilst bonding is completed with WEST SYSTEM epoxy. G5 will adhere to most prepared surfaces including wood, fibreglass and most metal and cures in 4-5 minutes.</p>	<p>G5 = 0.2kg Pack G5-2 = 2.0kg Pack G5-5 = 5.0kg Pack</p>
	<p><b>610 Six10 Adhesive Cartridge (190ml)</b> combines the strength and reliability of a two-part WEST SYSTEM® Brand Epoxy with point-and-shoot convenience. The self-metering coaxial cartridge dispenses a gap-filling structural epoxy that bonds tenaciously to wood, metals, fibreglass and concrete. The tube comes with a static mixer that lets you lay down a bead of thickened epoxy with any standard caulking gun.</p>	<p>610 = 1 Cartridge</p>
	<p><b>600-2 Static Mixers (for Six10 Adhesive)</b></p>	<p>600-2 = 2 of 600-10 = 10 of</p>
	<p><b>650 G/flex Epoxy Pack</b> A toughened, versatile, liquid epoxy for permanent waterproof bonding of fibreglass, ceramics, metals, plastics, damp and difficult-to-bond woods. Includes 118ml of G/flex 650 Resin, 118ml of G/flex 650 Hardener (236ml of mixed epoxy), and handling and repair instructions.</p>	<p>650-8 = 240g Pack 650-32 = 1 Litre Pack</p>
	<p><b>650 G/flex Resin Only</b></p>	<p>650-2GR = 4 Litre 650-CR = 20 Litre 650-ER = 180 Litre</p>
	<p><b>650 G/flex Hardener Only</b></p>	<p>650-2GH = 4 Litre 650-CH = 20 Litre 650-EH = 180 Litre</p>
	<p><b>650-K G/flex Epoxy Repair Kit</b> Kit contains 118ml G/flex 650 resin, 118ml G/flex 650 hardener, 2-reusable mixing stick/applicators, 2-12 cc syringes, 4 g-adhesive filler, 4-mixing cups, 1 pr-disposable neoprene gloves, 4-alcohol cleaning pads and complete handling and repair instructions.</p>	<p>1 kit</p>
	<p><b>655-K G/flex Thickened Epoxy Adhesive Repair Pack</b> Kit contains 125ml - G/flex 655 resin, 125ml - G/flex 655 hardener (250 ml mixed epoxy), 2-reusable mixing stick/applicators, 4-alcohol cleaning pads, 1 pr-disposable neoprene gloves, 10 mixing palettes and complete handling and repair instructions.</p>	<p>1 kit</p>
	<p><b>655 G/Flex Thickened Epoxy Adhesive Pack</b> A thickened, easy-to-use epoxy that permanently bonds fibreglass, ceramics, metals, plastics, damp and difficult-to-bond woods. G/flex is toughened to make structural bonds that absorb the stresses of expansion, contraction, shock and vibration. Glue resinous woods, exotic woods and a wide range of dissimilar materials.</p>	<p>655-32 = 1 Litre Pack</p>











	<b>655 G/Flex Thickened Epoxy Adhesive Resin Only</b>	655-2GR = 4 Litre 655-CR = 20 Litre 655-ER = 180 Litre
	<b>655 G/Flex Thickened Epoxy Adhesive Hardener Only</b>	655-2GH = 4 Litre 655-CH = 20 Litre 655-EH = 180 Litre
<b>Metering Dispensers</b>		
	<b>301 Mini Pump Set (5:1)</b> Specially designed for convenient and accurate dispensing of WEST SYSTEM 105 Resin and 205 or 206 Hardeners. The pumps mount directly on the resin and hardener containers and have been calibrated to deliver the correct working ratio of 5 parts by weight of resin to 1 part by weight of hardener with one stroke from each pump. <b>WARNING: DO NOT USE 301 MINI PUMPS WITH 207 OR 209 HARDENERS.</b>	301A = A Pack Size 301B = B Pack Size 301C = C Pack Size
	<b>303A Special Ratio Mini Pump Set (3:1)</b> Designed for convenient and accurate dispensing of WEST SYSTEM 105 Resin and 207 Special Coating Hardener or 209 Extra Slow Hardener. The mini pumps mount directly on the resin and hardener containers and have been calibrated to deliver the correct working ratio of 3 parts by weight of resin to 1 part by weight of hardener with one stroke from each pump. <b>WARNING: DO NOT USE 303 SPECIAL RATIO MINI PUMPS WITH 205 OR 206 HARDENERS.</b>	303A = A Pack Size 303B = B Pack Size 303C = C Pack Size
	<b>306-25 Model A Dispensing Pump (5:1 ratio)</b> For metering larger quantities of 105 Resin and 205 or 206 (5:1 ratio) Hardeners. The 306-25 Pump will reduce mixing time and waste on large projects. A carrying handle allows you to move the pump where the work is. Reservoirs hold one gallon of resin, one quart of hardener. Dispenses approximately 0.5 fl oz of resin/hardener per pump stroke (about 1 qt per minute).	306-25 = 1 Pump
	<b>306-23 Model A Dispensing Pump (3:1 ratio)</b> Similar to 306-25 Metering Pump described above. For metering 105 Resin and 207 Special Coating or 209 Extra Slow (3:1 ratio) Hardeners.	306-23 = 1 Pump
	<b>306-K Pump Rebuild Kit</b> Includes seals, balls, gaskets, springs, high-rise tubes with ferrules and new resin and hardener reservoirs with lids.	306-K = 1 Kit
	<b>309 Gear Pump (5:1 ratio)</b> For use with 205 or 206 (5:1 ratio) Hardeners. The 309 Gear Pump is designed and built by Gougeon Brothers for large projects and manufacturing operations. The home builder and professional alike will enjoy the efficiency of this high-volume pump. With continuous rotation of the crank, the metered resin and hardener can be delivered at up to five quarts per minute. Positive shutoff prevents resin and hardener loss through dripping spouts. Reservoirs hold two gallons of resin, one gallon of hardener.	309 = 1 Pump
	<b>309-3 Gear Pump (3:1 ratio)</b> Similar to 309 High-Capacity Gear Pump described above. For metering 105 Resin and 207 Special Coating or 209 Extra Slow (3:1 ratio) Hardeners.	309-3 = 1 Pump
<b>WEST SYSTEM Fillers</b>		
	<b>402 Milled Glass Fibre</b> A high density blended filler consisting of loose chopped glass and other fillers, intended for small semi structural repairs, filling voids, or small scale impact damage to glass fibre laminates. The finished repairs are incredibly strong, tough and resilient.	402 = 0.15kg 402A = 1.0kg 402B = 5.0kg
	<b>403 Microfibres</b> A fine fibre blend, is used as a thickening additive with resin/hardener to create a multi-purpose adhesive, especially for bonding wood. Epoxy thickened with microfibers has good gap-filling qualities while retaining excellent wetting/penetrating capability.	403 = 0.15kg 403A = 0.75kg 403B = 3.2kg 403C = 20.0kg
	<b>404 High-Density filler</b> Is a thickening additive developed for maximum physical properties in hardware bonding where high-cyclic loads are anticipated. It can also be used for filleting and gap filling where maximum strength is necessary.	404 = 0.25kg 404A = 1.75kg 404B = 10kg

	<p><b>405 Filleting Blend</b> This strong, wood-toned filler is good for use in glue joints and fillets on naturally finished wood. It mixes easily with epoxy and lets you create fillets that are smooth and require little sanding. Its color is a consistent brown, so 405 can be used to modify the shade of other WEST SYSTEM fillers.</p>	<p>405 = 0.15kg 405A = 0.70kg 405B = 5.0kg</p>
	<p><b>406 Colloidal Silica</b> Is a thickening additive used to control the viscosity of the epoxy and prevent epoxy runoff in vertical and overhead joints. 406 is a very strong filler that creates a smooth mixture, ideal for general bonding and filleting. It is also our most versatile filler. Often used in combination with other fillers, it can be used to improve strength, abrasion resistance, and consistency of fairing compounds, resulting in a tougher, smoother surface.</p>	<p>406 = 0,06kg 406A = 0.275kg 406B = 1.5kg 406C = 10.0kg</p>
	<p><b>407 Low-Density filler</b> Is a blended microballoon-based filler used to make fairing putties that are easy to sand or carve. Reasonably strong on a strength-to-weight basis. Cures to a dark red/brown color.</p>	<p>407 = 0.15kg 407A = 0.70kg 407B = 3.5kg 407C = 15.0kg</p>
	<p><b>409 Microsphere Blend</b> A pure white, hollow glass bubble based, low density filler designed for filling and fairing of fibreglass.</p>	<p>409 = 0.1kg 409A = 0.4kg 409B = 3.0kg</p>
	<p><b>410 Microlight™</b> Is the ideal low-density filler for creating a light, easily-worked fairing compound especially suited for fairing large areas. Microlight mixes with greater ease than 407 Low-Density filler or microballoons and is approximately 30% easier to sand. It feathers to a fine edge and is also more economical for large fairing jobs. Not recommended under dark paint or other surfaces subject to high temperatures. Cures to a tan color.</p>	<p>410 = 0.050kg 410A = 0.20kg 410B = 1.5kg</p>
<b>Additives</b>		
	<p><b>420 Aluminium Powder</b> Add between 5 to 10% by volume to provide protection from ultraviolet light in areas which will not be protected with other coatings and as a base for subsequent painting. Will substantially increase the hardness of the coated surface.</p>	<p>420 = 0.1kg</p>
	<p><b>421 Fire Retardant Additive</b> 421 is a fine white powder added to the epoxy in the ratio of one to one by weight. The cured material is a fire retardant composition for use in engine or galley areas. 421 Fire Retardant will greatly increase the viscosity of the epoxy and the composition requires trowelling or squeegeeing into place.</p>	<p>421 = 1.0kg</p>
	<p><b>422 Barrier Coat Additive™</b> A proprietary blend designed to improve the moisture exclusion effectiveness of WEST SYSTEM™ epoxy. 422 also increases the abrasion resistance and is an excellent additive for providing a barrier coating to help prevent gelcoat blistering. Add 20 to 25% by weight of 422 to the mixed epoxy.</p>	<p>422 = 0,5kg 422B = 3.0kg</p>
	<p><b>423 Graphite Powder</b> A fine black powder added to WEST SYSTEM epoxy (10% by volume) to produce a low friction exterior coating with increased scuff resistance, durability and mar resistant. Epoxy/graphite is commonly used as a coating on rudders and centreboards, or on the bottoms of racing craft that are dry sailed. The epoxy/ graphite mix can also be used in teak deck construction to simulate traditional seams in appearance and to protect the resin from sunlight.</p>	<p>423 = 0.2kg 423B = 3.0kg</p>
	<p><b>425 Copper Compound</b> 425 Copper Compound can be added to the mixed epoxy to provide a base coat for conventional bottom paint. When added to the epoxy at the rate of 80% by weight, the resultant hard surface increases the moisture exclusion effectiveness, abrasion resistance and provides some back up antifouling properties. Can be used for any coating application when a harder surface is required, e.g. coating moulds.</p>	<p>425 = 0.5kg 425B = 2.5kg 425C = 10.0kg</p>
<b>Colouring Additives</b>		
	<p><b>501 White Pigment, 502 Black Pigment, 505 Blue Pigment, 506 Grey Pigment</b> WEST SYSTEM colour pigments can be added to the epoxy to provide a base colour for a final finish system. The coloured surfaces also tend to highlight flaws and imperfections. Pigments should be added at a rate of approximately 3 to 5 % by weight and should only be added to the final coat of epoxy because the increased viscosity of the mix will impair the ability of the epoxy to penetrate and seal surfaces.</p>	<p>501 = 0.125kg, 501B = 1.0kg 502 = 0.125kg, 502B = 1.0kg 505 = 0.125kg, 505B = 1.0kg 506 = 0.125kg, 506B = 1.0kg</p>
<b>Graphite Fibres</b>		
	<p><b>701 Graphite Fibres / Tow 25mm</b> For adding strength to specific areas on centreboards, rudders, masts and models, etc.</p>	<p>701B = 304m</p>
<b>Glass Tape</b>		

	<b>450g/m<sup>2</sup> Biaxial Tape (441g/m<sup>2</sup> = 13oz)</b> For use in taping seams, joints and small repairs.	<b>727A = 125mm x 5m</b> <b>727B = 125mm x 90m</b>
	<b>175g/m<sup>2</sup> Plain Weave Tape (170g/m<sup>2</sup> = 5oz)</b> For use in taping seams and joints.	729A = 25mm x 10m 729B = 25mm x 50m 730A = 50mm x 10m 730B = 50mm x 50m 731A = 75mm x 10m 731B = 75mm x 50m 732A = 100mm x 10m 732B = 100mm x 50m 733A = 150mm x 10m 733B = 150mm x 50m
<b>Biaxial Glass Fabric</b>		
	<b>300 g/m<sup>2</sup> ±45° Biaxial (305g/m<sup>2</sup> = 9oz)</b> General purpose fabric for use in sheathing, repair, in mould laminating, etc.	<b>736-5 = 1.265m x 5m</b> <b>736-10 = 1.265m x 10m</b> <b>736-25 = 1.265m x 25m</b> <b>736-50 = 1.265m x 50m</b>
	<b>610g/m<sup>2</sup> ±45° Biaxial (610g/m<sup>2</sup> = 18oz)</b> General purpose fabric for use in sheathing, repair, in mould laminating, etc.	<b>738-5 = 1.25m x 5m</b> <b>738-10 = 1.25m x 10m</b> <b>738-25 = 1.25m x 25m</b> <b>738-50 = 1.25m x 50m</b>
	<b>450g/m<sup>2</sup> ±45° Biaxial (441g/m<sup>2</sup> = 13oz)</b> General purpose fabric for use in sheathing, repair, in mould laminating, etc.	<b>739-5 = 1.25m x 5m</b> <b>739-10 = 1.25m x 10m</b> <b>739-25 = 1.25m x 25m</b> <b>739-45 = 1.25m x 45m</b> <b>739-270 = 0.27m x 50m</b> <b>739-500 = 0.5m x 50m</b>
<b>Glass Cloth</b>		
	<b>135g/m<sup>2</sup> Plain Weave Glass Cloth (135g/m<sup>2</sup> = 4oz)</b> For use in sheathing lightweight structures such as canoes and models.	<b>740-5 = 1m x 5m</b> <b>740-10 = 1m x 10m</b> <b>740-25 = 1m x 25m</b> <b>740-50 = 1m x 50m</b> <b>740-100 = 1m x 100m</b>
	<b>200g/m<sup>2</sup> Plain Weave Glass Cloth (203g/m<sup>2</sup> = 6oz)</b> For use in general sheathing work on hulls and decks, etc.	<b>741B = 1m<sup>2</sup></b> <b>741-5 = 1m x 5m</b> <b>741-10 = 1m x 10m</b> <b>741-25 = 1m x 25m</b> <b>741-50 = 1m x 50m</b> <b>741-100 = 1m x 100m</b>
	<b>200g/m<sup>2</sup> Twill Weave Glass Cloth (203g/m<sup>2</sup> = 6oz)</b> For use in general sheathing work on hulls and decks, has good drapability.	<b>742-5 = 1m x 5m</b> <b>742-10 = 1m x 10m</b> <b>742-25 = 1m x 25m</b> <b>742-50 = 1m x 50m</b> <b>742-100 = 1m x 100m</b>
	<b>280g/m<sup>2</sup> Twill tapered edges (271g/m<sup>2</sup> = 8oz)</b> For use in general sheathing and re-laminating work and general repairs to boat structures. Very good drapability.	<b>743-5 = 1m x 5m</b> <b>743-10 = 1m x 10m</b> <b>743-25 = 1m x 25m</b> <b>743-50 = 1m x 50m</b> <b>743-100 = 1m x 100m</b>
	<b>190g/m<sup>2</sup> C/foot Weave Glass Cloth (203g/m<sup>2</sup> = 6oz)</b> For use in sheathing surf and sailboards, rudders and centreboards.	<b>745-5 = 1m x 5m</b> <b>745-10 = 1m x 10m</b> <b>745-25 = 1m x 25m</b> <b>745-50 = 1m x 50m</b> <b>745-100 = 1m x 100m</b>
	<b>260g/m<sup>2</sup> Woven Roving (271g/m<sup>2</sup> = 8oz)</b> General purpose economic glass cloth.	<b>746-5 = 1m x 5m</b> <b>746-10 = 1m x 10m</b> <b>746-25 = 1m x 25m</b> <b>746-50 = 1m x 50m</b> <b>746-100 = 1m x 100m</b>
<b>Peel Ply</b>		
	<b>Peel Ply</b> Peel Ply is a finely woven fabric treated with a release agent to which epoxy will not bond. Excellent for providing a release and reducing subsequent sanding prior to applying more epoxy.	<b>773 = 0.5m x 100m</b> <b>774-1 = 1m x 1m</b> <b>774 = 1m x 91m</b> <b>775-1 = 1.25m x 1m</b> <b>775-125 = 1.25m x 100m</b> <b>775-50 = 0.05 x 100m</b> <b>775-100 = 0.1m x 100m</b>
<b>Application Tools</b>		

	<b>790 180mm Foam Roller Cover</b> 180mm wide, 45mm diameter, foam roller cover.	<b>790 = 1 of</b> <b>790-6 = 6 of</b>
	<b>791 180mm Roller Frame</b> 180mm wide bird cage roller frame designed for use with the 790 Roller cover.	<b>1</b>
	<b>800-2 75mm Foam Roller Cover</b> 75mm wide foam roller cover - ideal for coating epoxy in small areas.	<b>800-2 = 2 of</b> <b>800-12 = 12 of</b>
	<b>801 75mm Roller Frame</b> Reusable 75mm wide roller frames for use with the 800 roller covers.	<b>1</b>
	<b>802 Roller Pan</b> Flexible plastic roller pan allows cured epoxy to 'pop out', so the pan can be reused. Eliminates the need for liners.	<b>1</b>
	<b>803 Glue Application Brushes (pack of 5)</b> Handy, disposable, glue brushes with a wooden handle. These brushes are used for a wide variety of gluing and coating applications.	<b>803-5 = 5 of</b>
	<b>804 Mixing Sticks</b> 150mm x 18mm wide rounded wooden mixing sticks for blending epoxy and perfect for small radii fillets	<b>804 = Box of 100</b> <b>804-25 = pack of 25</b>
	<b>804B Wooden Stirrers</b> 300mm x 27mm, square edged wooden stirrers will ensure thorough mixing when high percentages of fillers are incorporated into the epoxy. Strong, durable stirrers that are ideal for scraping excess epoxy from surfaces.	<b>804B-5 = Pack of 5</b>
	<b>805 Graduated Mixing Pot</b> Strong reusable 800ml mixing pots graduated in 50ml divisions. When cured, solid epoxy easily "pops out" of these reusable plastic mixing pots.	<b>800ml</b>
	<b>807 Syringes</b> Reusable syringes which can be loaded with the epoxy for injecting into difficult working areas. Ideal for hardware bonding and plywood repairs.	<b>807-2 = 1 x 10ml + 1 x 50ml</b> <b>807-10 = 2 x 10ml</b> <b>807-50 = 2 x 50ml</b>
	<b>808 Plastic Squeegees</b> Lightweight, reusable squeegees for fairing and filling applications. Double-edged, 90mm x 150mm.	<b>898-2 = 2 of</b> <b>808-12 = 12 of</b>
	<b>809 Notched Spreaders (pack of 2)</b> 110mm x 110mm Lightweight, reusable spreaders with 3mm, 4mm and 6mm notches on three sides for quickly applying modified epoxy at a constant rate. Useful when laminating large panels	<b>809-2 = 2 of</b> <b>809-36 = box of 36</b>
	<b>811 50mm Paddle Roller</b> Ridged aluminium rollers for thoroughly wetting-out fabrics with epoxy. Diameter 22mm.	<b>811 = 1 x 50mm</b> <b>811B = 1 x 150mm</b>

	<b>817 25mm Finishing Brush</b> High quality brush for varnish or paint application.	<b>817-1 = 1 x 25mm</b> <b>817-2 = 1 x 50mm</b>
	<b>818 Laminating Brush</b> Good quality firm bristle brush for applying epoxy over the laminating area and for consolidating the fabric. Available in 50mm	<b>1</b>
<b>Cleaning &amp; Safety Equipment</b>		
	<b>820 Resin Removing Cream</b> Formulated to remove uncured epoxy from skin. Available in 250 dispensers and 1kg plastic pots.	<b>820 = 250ml</b> <b>820B = 1/0kg</b>
	<b>831 Barrier Cream</b> An aerosol containing a non-irritant, multi-purpose barrier cream which has special bactericidal ingredients to minimise the risk of skin infection. Protects against resins, oils, grease and petroleum spirits.	<b>831 = 250ml</b> <b>831B = 1.0kg</b>
	<b>832 Disposable Protective Nitrile Gloves</b> Lightweight, seamless disposable gloves help prevent exposure to chemicals. Excellent protection with good finger sensitivity and dexterity. CE marked.	<b>832 = 50 Pairs</b> <b>832-5 = 5 Pairs</b>
	<b>834 Reusable Gloves</b> Heavy-duty rubber gloves offer superior tear and abrasion resistance and are liquid proof. Can be reused. CE marked.	<b>Per pair</b>
	<b>850 Cleaning Solvent</b> A specially blended cleaning solvent for removing uncured epoxy from tools, boat and workshop surfaces. Also excellent for cleaning contaminants from cured epoxy surfaces.	<b>850 = 1 Litre</b> <b>850B = 2.5 Litre</b>
	<b>855 Cleaning Solution</b> A safe, easy to use cleaning solution developed to remove uncured epoxy from tools workbenches, minipumps etc. Can also be used to wash off amine blush.	<b>855 = 1 Litre</b> <b>855B = 5 Litre</b>
<b>Sundry Items</b>		
	<b>875 Scarfer<sup>®</sup></b> A unique tool designed by Gougeon Brothers for cutting accurate scarf joints in plywood up to 3/8" thick. Attaches easily to most circular saws and is easily removed.	<b>875 = 1 of</b>
	<b>885 Vacuum Bagging Kit + Instructions</b> A complete starter kit for room temperature repairs and small laminating projects up to 1.2m <sup>2</sup> in size. The kit includes: Venturi vacuum generator (with bronze muffler), Vacuum Cups (3), 6mm i/d, Vacuum Tubing (3m), Vacuum Gauge, Junction "T" Barbs (2), Release Fabric (1.4m <sup>2</sup> ), Breather Fabric (1.4m <sup>2</sup> ), Vacuum Bag Film (1.4m <sup>2</sup> ), Vacuum Bag Sealant (7.5m), Instruction leaflet, 002-150 VACUUM BAGGING TECHNIQUES.	<b>885 = Per Kit</b>
	<b>Vacuum Cups</b>	<b>885-3 = Pack of 3</b>
	<b>Venturi Vacuum Generator (With Silencer)</b> The venturi generator develops over 65kPa of vacuum (0.065MPa) and is designed to run off of conventional shop air compressors delivering at least 0.42MPa. Some item specifications may vary.	<b>885-6 = 1 of</b>

	<b>Replacement Silencer</b>	<b>885-7 = 1 of</b>
<b>Publications &amp; Videos</b>		
	<b>Fibreglass Repair Video</b> A guide to structural repair on fibreglass boats. Covers repairs to cored and non-cored panels and how to apply gelcoat over epoxy repairs.	<b>002-894 = 1 of</b>
	<b>Gelcoat Blisters Video</b> A guide for repairing and preventing gelcoat blisters on fibreglass boats. Includes an analysis of the factors contributing to blister formation and steps for preparation, drying, repairing and coating for moisture protection.	<b>002-896 = 1 of</b>
	<b>How-To DVD</b> A compilation of three instructional videos demonstrating basic handling and advanced techniques, including Basic Application Techniques; Fibreglass Repair with WEST SYSTEM Epoxy and Gelcoat Blister Repair with WEST SYSTEM Epoxy. Interactive menus allow for easy navigation through these subjects.	<b>002-898 = 1 of</b>
	<b>Gougeon Brothers on Boat Construction</b> Decades of experience building with wood and epoxy are compiled in this 5th edition, completed in 2005. New and updated material is combined with proven technology in a revised layout for navigation. Extensive chapters on hardware bonding, construction methods, safety and tools are described with the aid of hundreds of detailed illustrations and photographs. Used as a textbook in boatbuilding schools. Over 100,000 copies in print.	<b>002 = 1 of</b>
	<b>Advanced Vacuum Bagging Techniques</b> A step-by-step guide to vacuum bag laminating, a technique for clamping wood, core materials and synthetic composites bonded with WEST SYSTEM epoxy. Discusses theory, moulds, equipment and techniques used to build composite structures.	<b>002-150 = 1 of</b>
	<b>Fibreglass Boat Repair &amp; Maintenance</b> A complete guide to repair fibreglass boats with WEST SYSTEM epoxy. Includes illustrated procedures for structural reinforcement, deck and hull repair, hardware installation, keel repair and teak deck installation.	<b>002-550 = 1 of</b>
	<b>Gelcoat Blisters: Diagnosis, Repair &amp; Prevention</b> A guide for repairing and preventing gelcoat blisters in fibreglass boats with WEST SYSTEM epoxy. Includes an analysis of the factors that contribute to blister formation and illustrated steps for preparation, drying, repairing and coating for moisture protection.	<b>002-650 = 1 of</b>
	<b>Final Fairing &amp; Finishing</b> Techniques for fairing wood, fibreglass and metal surfaces. Includes fairing tools, materials and a general guide to finish coatings	<b>002-740 = 1 of</b>
	<b>Wooden Boat Restoration &amp; Repair</b> An illustrated guide to restore the structure, improve the appearance, reduce the maintenance and prolong the life of wooden boats with WEST SYSTEM epoxy. Includes information on dry rot repair, structural framework repair, hull and deck planking repair, hardware installation with epoxy and protective coating.	<b>002-970 = 1 of</b>